## Technical Data for Suction Filters and Strainers with Relief Valve

Filter	Rated Capacity	<u>Connect</u>	<u>Dimensions</u>				Diff. Drop Across Filter	Approx. Ship			
Number	ĠPM	Size	Туре	Filtering Media			3	Diameter	Height	Inches of Hg	Weight
00211	5	1/2" N.P.T.	Male Fitting	100 Mesh Stainless Steel			Steel	2 15/16"	4 7/16"	.64	.7 lb.
04111	5	3/4" N.P.T.	Hex Nut	"	"	"	"	2 15/16"	4 5/8"	.46	.8 lb.
04211	5	3/4" N.P.T.	Male Fitting	11	11	"	"	2 15/16"	4 7/16"	.46	.7 lb.
11111	10	1" N.P.T.	Hex Nut	11	"	"	"	2 15/16"	5 3/16"	.64	1.1 lb.
11211	10	1" N.P.T.	Male Fitting	"	"	"	11	2 15/16"	4 15/16"	.64	.9 lb.
11311	10	1 5/16" O.D. Tube	O-Ring	11	"	"	"	2 15/16"	4 9/16"	.66	.8 lb.
22111	20	1 ¼" N.P.T.	Hex Nut	"	"	"	"	3 3/8"	7 11/16"	.46	1.8 lb.
22211	20	1 ¼" N.P.T.	Male Fitting	"	II	"	"	3 3/8"	7 7/16"	.46	1.4 lb.
22311	20	1 5/8" O.D. Tube	O-Ring	"	"	"	"	3 3/8"	7 1/16"	.48	1.4 lb.
33111	30	1 ½" N.P.T.	Hex Nut	"	"	"	11	3 5/8"	8 3/4"	.60	2.1 lb.
33211	30	1 ½" N.P.T.	Male Fitting	11	"	"	"	3 5/8"	8 7/16"	.60	1.7 lb.
33311	30	1 7/8" O.D. Tube	O-Ring	"	"	"	11	3 5/8"	8 1/16"	.62	1.7 lb.
53111	50	1 ½" N.P.T.	Hex Nut	11	"	"	"	4 1/4"	9 3/4"	1.28	2.7 lb.
53211	50	1 ½" N.P.T.	Male Fitting	11	"	"	"	4 1/4"	9 7/16"	1.28	2.2 lb.
53311	50	1 7/8" O.D. Tube	O-Ring	"	"	"	"	4 1/4"	9 1/16"	1.52	2.2 lb.
55111	50	2" N.P.T.	Hex Nut	11	"	11	11	4 1/4"	9 13/16"	.58	2.9 lb.
55211	50	2" N.P.T.	Male Fitting	"	"	"	"	4 1/4"	9 1/2"	.58	2.3 lb.
55311	50	2 3/8" O.D. Tube	O-Ring	"	"	"	"	4 1/4"	9 1/16"	.60	2.3 lb.
66111	75	2 ½" N.P.T.	Hex Nut	"	"	"	"	4 13/16"	11 1/8"	.64	3.8 lb.
77111	100	3" N.P.T.	Hex Nut	"	"	"	"	5 11/16"	12 1/4"	.64	5.3 lb.

- Filtering Media: 100 Mesh (141 Micron Nominal) Stainless Steel Wire Cloth backed with 16 Mesh Wire Cloth
- Differential Drop at Rated Capacity Using 225 SSU (Approx.) Petroleum Base Oil Flowing at Five Feet Per Second
- Relief Valve Set to Open at 5" Hg ± 10% Vacuum Differential—Other Settings Are Available
- Standard Connection Type: N.P.T. Hex Nut/ N.P.T.F. Male Fitting/ O-Ring
- Standard Filtering Media Sizes Available: 30 Mesh, 60 Mesh, 100 Mesh, 200 Mesh. Special Mesh Sizes Available On Request



Manufacturers of Suction Filters, Strainers, & Return-Line Flow Diffusers

940 Anita Avenue ♦ Antioch, IL 60002 ♦ Phone: 847.838.6723 ♦ Fax: 847.838.6725 ♦ Email: domsinc@core.com ♦ Website: domsinc.com